

- ✓ 2-in-1
- ✓ Versatile in use
- ✓ High precision rotor arm/rotor unit
- ✓ High quality swivel or toggle swivel
- ✓ Easy flip function



TECHNICAL DATA


Pressure 275 bar
Temperature 120°C
Inlet G3/8" F

FEATURES

Flip function

Effortless turning of the wheels / 2-in-1 function. The Hurricane Flip can be converted from a floor cleaner to an undercarriage cleaner in just a few simple steps.

Part No. 80.9030 ø300 Part No. 80.9045 ø520



HURRICANE FLIP ø520 FEATURES

High quality swivel

DYF swivel with reinforced, self-lubricating stainless steel ball bearings and a carbide sealing system for high speed rotation.

Part No. 58.323



High precision rotor arm

The rotor arm, which is manufactured in an automated welding process is robust and balanced.

Part No. 82.942 ø470 mm



HURRICANE FLIP ø300 FEATURES

High precision rotor unit

DYF swivel with reinforced, self-lubricating bearings made from stainless steel and a carbide sealing for high RPM. New rotor arm design with low profile for cleaning jobs with limited clearance.


Part No. 58.913



Toggle swivel

The proven toggle joint makes easy and effortless cleaning possible. Positioned on the side of the housing, this special construction enables cleaning under the vehicle.

Part No. 42.906



HP-Coupling

The quick coupler easily connects or disconnects the lance to the rotor unit for storage purposes or for use with other equipment.

Part No. 70.021 + 70.904



140



100

Important: Do not use unprotected!

Hurricane Flip

Name	Part No.	ø	min. Clearance	Weight	Rotorarm	HP-Nozzles	HP-Gun	Stainless Steel Caster
HURF-300	78.602	300	105 mm	5.3 kg	2x 1/8" NPTF	2x 18.15030	1x	3x ø60
HURF-520	80.606	520	145 mm	13.0 kg	2x 1/8" NPTF	2x 18.15030	1x	4x ø60

Other nozzles sizes please order separately.